



CATALOGUE

Cryo Bio System was founded in 1987 and is the human division of IMV Technologies.

Exclusively dedicated to Life Science and Biodiversity, Cryo Bio System strives to provide scientists and physicians with IMV Technologies' expertise in the field of cryopreservation of biological samples, with innovative and High Security products for:

- Biorepositories, epidemiological research
- Blood transfusion haemovigilance
- Cell culture and genetic therapy units
- The pharmaceutical industry
- Assisted Reproductive Technologies
- Genomics and proteomics
- Medico-legal storage
- Military medicine
- Biodiversity (animal and plant-based germplasm conservation)

Cryo Bio System currently operates in over 80 countries through five subsidiaries in the USA, India, Italy, the Netherlands and China, as well as a network of efficient distributors, focusing on product quality and a keeping close to its clients to best meet their requirements.

Cryo Bio System...

High Security, a unique concept



Safety

No risk of cross-contamination between samples, the outside environment (LN2) and the operator.



Biocompatibility

Use of biocompatible, non toxic ionomeric resin, with no plastic agent or by-product.



Traceability

Color code identification and LN2-proof printed labels/jackets (link with sample, patient's clinical and medical data).



Optimization

Storage in straws or goblets for space optimization.

CONTENTS

■ CONSUMABLES

CBS™ High Security sperm straw with tripartite plug 0.3 and 0.5 ml	6
CBS™ High Security embryo and sperm straw with tripartite plug 0.3 ml	8
CBS™ High Security 2 ml tissue straw	8
PETG sperm straw	9
PETG embryo straw	9
CBS™ High Security Vitrification straw	10
CBS™ High Security Tube	12
LEJA slides	14
Injection, holding and biopsy pipettes	15

■ ACCESSORIES

Micro-aspirator	18
Makler® counting chamber	18
Identification rods for CBS™ 0.3 ml straws	19
Identification and obturating rods for PETG straws	19
2D colored inserts	19
BMP 21 and BMP 51 printers	20

■ STORAGE

Visotubes and goblets	24
Canisters	26
Identification rods for visotubes	27
Insulated transport box	27

■ EQUIPMENT

Nano-Digitcool	30
Digitcool controlled-rate freezers	31
Craft™ pump	32
SYMS	32
SYMS III	33
SYSO	34
PACE	35
MAPI	36
DIVA	37
Integral HSV	38



CONSUMABLES

CBS™ High Security sperm straw with tripartite plug 0.3 and 0.5 ml
CBS™ High Security embryo and sperm straw with tripartite plug 0.3 ml
CBS™ High Security 2 ml tissue straw
PETG sperm straw
PETG embryo straw
CBS™ High Security Vitrification straw
CBS™ High Security Tube
LEJA slides
Injection, holding and biopsy pipettes

CBS™ High Security sperm straw with tripartite plug 0.3 and 0.5 ml

CE marked according to directive 93/42/CE
FDA registration



DESCRIPTION

Human sperm freezing and cryopreservation. With their distinctive characteristics, filling and sealing methods, CBS™ High Security straws are designed for cryopreservation of human biological samples, guaranteeing perfect tightness, specifically in liquid nitrogen. Manufactured from biocompatible materials, they are suited to Assisted Reproductive Technologies, and more specifically for embryo and sperm cryopreservation. The CBS™ High Security straw is a clear flexible tube made of ionomeric resin.

TECHNICAL CHARACTERISTICS

Length: 133 mm
Internal diameter: 2.5 mm
Sterilization by irradiation.

024856	Box of 100 sterile clear filling nozzles	100
014175	Permanent black markers	2
016730	Sterile connection tubing for syringe (individually packed)	10
016731	Sterile connection tubing for syringe (packed in units of 5)	5



BIOBANKING APPLICATION (non sterile)

021661 CBS™ High Security 0.3 ml straw colored rod and white jacket 300


CBS™ High Security 0.3 ml straw colored identification rod and white jacket 300


Blue	Red	Yellow	White	Green	Purple
021661 ●	021662 ●	022189 ●	022539 ○	022540 ●	022541 ●

CBS™ High Security 0.5 ml straw colored plug and white jacket 9000

Grey	Red	Green	Blue	Yellow	Orange	White
014626 ●	014627 ●	014628 ●	014629 ●	014630 ●	014631 ●	014657 ○

015047 Blue emptying rod for CBS™ High Security straws 1000





CBS™ 0.3 ml model


This straw comprises two separate parts separated by a white plug. The first part contains semen and has a capacity of 0.3 ml. The second part accommodates the colored identification rod and is used for holding when handling liquid nitrogen.

010287	CBS™ High Security 0.3 ml sperm straw white plug	20
010288	CBS™ High Security 0.3 ml sperm straw white plug	100

For MAPI and PACE

CBS™ High Security 0.3 ml sperm straw colored identification rod and white jacket	75
---	----

Red	White	Yellow	Blue	Green	Violet
017797 ●	017798 ○	017799 ●	017800 ●	017801 ●	017802 ●



CBS™ 0.5 ml model

This model features the same technical specifications as the 0.3 ml straw, except that it has a capacity of 0.5 ml and the external surface of the plug is colored.

014651	CBS™ High Security 0.5 ml sperm straw white plug	20
014650	CBS™ High Security 0.5 ml sperm straw white plug	100

CBS™ High Security 0.5 ml sperm straw with colored cotton plug	100
--	-----

Red	Yellow	Green	Blue	Orange	Grey
016584 ●	016611 ●	016612 ●	016613 ●	016614 ●	016615 ●

For MAPI and PACE

CBS™ High Security 0.5 ml sperm straw colored identification rod and white jacket	75
---	----

White	Blue	Green	Yellow	Orange	Red
021954 ○	021955 ●	021956 ●	021957 ●	021958 ●	021959 ●

30 mm weighted identification rods for 0.3 ml straws

Yellow	Green	Blue	Orange	White	Red
019021 ●	019022 ●	019023 ●	019024 ●	019025 ○	019026 ●

Outer identification jacket


Red	White	Orange	Green	Blue	Yellow	Clear
010272 ●	010273 ○	010274 ●	010275 ●	010276 ●	010277 ●	014939 ○

CBS™ High Security embryo and sperm straw with tripartite plug 0.3 ml

CE marked
FDA 510(k) premarket notification clearance for the USA # K002595

025292 CBS™ High Security embryo and sperm straw with tripartite plug 0.3 ml

20



DESCRIPTION

The CBS™ High Security embryo and sperm straw with braided plug is specifically designed for long-term cryopreservation of human biological samples, including liquid nitrogen. Made of biocompatible materials, it is suited to Assisted Reproduction procedures, and more specifically to embryo and sperm cryopreservation. *Single packaging. Pack of 5 blisters of 4 units.*

TECHNICAL CHARACTERISTICS

Length: 133 mm
Internal diameter: 2.5 mm.
Sterilization by irradiation.

30 mm weighted identification rods

10

Yellow	Green	Blue	Orange	White	Red
019021	019022	019023	019024	019025	019026

024856 Box of sterile clear filling nozzles

100



The CBS™ filling nozzle ensures a leak-proof environment as it fully isolates the sealing zone from any contact with fluid as the biological sample is drawn in.

CBS™ High Security 2 ml tissue straw

CE marked

018960 CBS™ High Security 2 ml tissue straw

20



DESCRIPTION

Cryopreservation of tissue fragments.
CBS™ High Security 2 ml tissue straws are identified with labels with liquid nitrogen-proof ink and sticker. *Single packaging. Pack of 5 blisters of 4 units.*

TECHNICAL CHARACTERISTICS

Sterilization by irradiation.

PETG sperm straw

010261	Transparent PETG 0.25 ml sperm straw	100
014550	Transparent PETG 0.5 ml sperm straw	100
007342	Yellow sterile (13 mm) sealing and identification rods	20



DESCRIPTION

Freezing and storing human sperm PETG sperm straws are clear flexible straws made of a copolymer.


- The section which holds semen has a volume of 0.21 ml or 0.47 ml.
- The other section is used as an aspiration zone during filling.

TECHNICAL CHARACTERISTICS

- 0.25 ml straw
Length: 133 mm
Internal diameter: 1.6 mm
 - 0.5 ml straw
Length: 133 mm
Internal diameter: 2.5 mm
- Sterilization by irradiation.*

PETG embryo straw

006433	5 blister packs of 20 rigid embryo straws - 91 mm
006578	5 blister packs of 20 rigid embryo straws - 133 mm
014102	5 blister packs of 20 flexible embryo straws - 91 mm
014103	5 blisters packs of 20 flexible embryo straws - 133 mm



DESCRIPTION

PETG embryo straws are flexible or rigid clear tubes made of copolymer. The PETG embryo straws are closed at one end by a double-woven cotton plug, enclosing a dose of powder that polymerizes when in contact with liquid.

Blisters of 4 x 5 units.

TECHNICAL CHARACTERISTICS

- 0.15 ml for 91 mm long straws
 - 0.25 ml for 133 mm long straws
- The internal diameter is 1.6 mm for both models.
Sterilization by irradiation.

The 91 mm straws are closed with 42 mm identification rods and the 133 mm straws are closed with 13 mm identification and sealing rods (p.19)

CBS™ High Security Vitrification straw

CE marked
FDA 510(k) premarket notification clearance for the USA
K092398 for 4-8 cell and blastocyst stage embryos



DESCRIPTION

Vitrification of embryos

The kit is comprised of 3 parts:

- a transparent High Security Vitrification ionomeric resin straw;
- a capillary tube with a transparent gutter and co-injected colored handling rod;
- a blue insertion device.

Individually packaged. Blister pack of 4 kits.


TECHNICAL CHARACTERISTICS

Sterilization by irradiation.



Blister of 4 CBS™ High Security Vitrification straws

Red	White	Yellow	Pink	Blue	Green
025246 ●	025247 ○	025248 ●	025249 ●	025250 ●	025251 ●



- 027636** Box of 5 opening devices for CBS™ High Security Vitrification straw
027172 Opening set (holder + device) for CBS™ High Security Vitrification straw



DESCRIPTION

The opening device for CBS™ High Security Vitrification straws has been designed exclusively to open CBS™ High Security Vitrification straws. It is an ambidextrous device. It can be held either directly in the hand or using a "holder" (an accessory designed to keep the user further from the liquid nitrogen).

- 027807** Integral HSV Vitrification Unit



DESCRIPTION

The INTEGRAL HSV vitrification unit is designed for vitrification, packaging and opening of CBS™ High Security Vitrification straws in the following applications:

- Reproductive Biology Laboratories

For more information: p.38

CBS™ High Security Tube

COMPLIANCE WITH INTERNATIONAL STANDARDS

Compliant with CE standards according to the European Medical Devices Directive 93/42/CE modified 2007/47/CE (Classe IIa).

022252 Bag of 20 sterile CBS™ High Security Tubes

023722 Bag of 50 sterile CBS™ High Security Tubes

022251 Bag of 100 non-sterile CBS™ High Security Tubes



DESCRIPTION

The unique fully secured system for storage in liquid nitrogen.

CBS™ High Security tubes are derived from the CBS™ high security concept designed for optimum sample preservation. Made of biocompatible resin, CBS™ tubes eliminate concerns related to cross-contamination and issues induced by storage in liquid nitrogen.

Once sealed with the SYMS III sealer, the CBS™ High Security tube will be placed in storage boxes and in current storage systems.

TECHNICAL CHARACTERISTICS

Usable working volume: 1.2 mL

Dimensions: 48 mm, Ø 11.8 mm

Sterilization by irradiation.



SCOPE OF APPLICATION

- Preservation of fertility (ovarian and testicular tissue, and sperm) for Assisted Reproductive Technologies
- Biological tissue banks for clinical phase or research
- Blood banks and blood transfusion centers
- Cell and genetic therapy (clinical phase and therapeutic applications)
- Packaging of vaccines and heat-sensitive drugs

SAFETY

- Full seals eliminate risks of cross-contamination of the sample and its environment
- Validated as leak-proof and shatter-proof in all cryogenic temperatures including temperatures as low as liquid nitrogen phase
- Indestructible under normal conditions of use



TRACEABILITY OPTIONS

- Colored inserts for simple identification in cryogenic environments
- 2D data matrix coded inserts
- Compatible with cryoresistant labels

COMPATIBILITY

- Standard racks, boxes (9x9 or 10x10), canes
- Manual or automatic filling systems
- Programmable freezers (URL link: Digitcool line)
- Cryogenic storage conditions for use in:
 - o Liquid nitrogen
 - o Vapor phase
 - o Mechanical freezers

024922 SYSO



DESCRIPTION

The SYSO opening device can be used under laminar flow and is designed to open CBS™ High Security tubes with a hot wire.

For more information: p.34

023836 Autoclavable scissors for CBS™ High Security Tubes



LEJA slides

026853

CE marked
SC-10-01-04-B
10 µm 4 wells - 4X25
2 µl / analysis

026854

SC-12-01-C
12 µm 2 lateral wells - 4X25
4 µl / analysis

026855

CE marked
SC-20-01-C
20 µm 2 lateral wells - 4X25
6 µl / analysis

026354

CE marked
SC-20-01-02-B
20 µm 2 wells - 4X25
6 µl / analysis

026355

CE marked
SC-20-01-04-B CE
20 µm 4 wells - 4X25
3 µl / analysis

026357

CE marked
SC-100-01-02-A
100 µm 2 high precision wells - 4X25
30 µl / analysis

026857

CE marked
SC-100-01-02-B
100 µm 2 wells - 4X25
30 µl / analysis



026853



026854



026855



026354



026355



026357 - 026857

DESCRIPTION

High quality disposable counting chambers for sperm analysis.

Due to their special characteristics, Leja slides will both save time and increase the level of accuracy and precision of sperm analysis.

All slides are covered with a special coating to prevent air bubbles and to prevent the sample from bonding to the chamber surface.

The resin and ink are both non toxic. Leja slides have an excellent low limit of quantification and can handle high sperm concentrations.

This has a direct clinical impact: you will be better prepared to determine the thresholds for the various procedures of Assisted Reproduction Technologies (waiting for natural conception, intrauterine insemination, in-vitro fertilization and intracytoplasmic semen injection) and to decide on the best treatment option for a couple.

The high level of accuracy and precision of the Leja slides will allow your results to be compared with scientific data from other laboratories in regards to the relationship between semen parameters (concentration, motility, viscosity) and fertility.

TECHNICAL CHARACTERISTICS

Slides with 2 or 4 chambers

Depth: 10, 12, 20 or 100 microns



Injection, holding and biopsy pipettes

CE marked

Their unique shape and taper provide for smooth movement of its content.
Individually packed in boxes of 10 units.
Sterilization by irradiation.

INJECTION PIPETTES



022166	Injection pipette – 20° angle	10
022167	Injection pipette – 30° angle	10

DESCRIPTION
Injection pipettes are used to perform intracytoplasmic sperm injection (ICSI).

HOLDING PIPETTES



022168	Holding pipette – outer ø 100 µm – 20° angle	10
022169	Holding pipette – outer ø 100 µm – 30° angle	10
022170	Holding pipette – outer ø 120 µm – 20° angle	10
022171	Holding pipette – outer ø 120 µm – 30° angle	10

DESCRIPTION
Holding pipettes are designed to hold an oocyte or embryo in position during ICSI and other micromanipulation procedures.

BLASTOMERE BIOPSY PIPETTES



022172	Pipette for blastomere biopsy – 30° angle	10
--------	---	----

DESCRIPTION
Blastomere biopsy pipettes are designed to remove blastomeres from embryos for preimplantation genetic diagnosis (PGD).

	Angle	Inner diameter	Outer diameter	Tip to angle length
Injection	20° / 30°	4.5-5.0 µm	7 µm	0.55 mm
Holding	20° / 30°	15-20 µm	100-119 µm / 120-130 µm	0.65 mm
Blastomere biopsy	30°	28-32 µm	31-35 µm	0.55 mm

CONSUMABLES



ACCESSORIES

Micro-aspirator
Makler® counting chamber
Identification rods for CBS™ 0.3 ml straws
Identification and obturating rods for PETG straws
2D colored inserts
BMP 21 and BMP 51 printers

Micro-aspirator

014498 Micro-aspirator (comes with two adapters and tubing)



DESCRIPTION

Manual straw filling.

The micro-aspirator is used to manually fill all straws manufactured by Cryo Bio System without any risk of contamination.

014500 Micro-aspirator adapter and tubing

Makler[®] counting chamber

016261 Makler[®] counting chamber (complete with cover glass and grid)

016262 Spare cover disc with grid



DESCRIPTION

Quick semen analysis.

Counting chamber and flat disc made of optical glass for sperm count and testing.

Reusable: easy to clean with bleach-free disinfectant.

The 10 micron depth eliminates any blurred area and enables sperm motility.

The specimen is analyzed horizontally. The grid is positioned over the disc. Therefore, there is no need to insert and remove the grid under the microscope lens.

Identification rods for CBS™ 0.3 ml straws

Bag of 30 mm weighted identification rods

10

Yellow 019021	Green 019022	Blue 019023	Orange 019024	White 019025	Red 019026
------------------	-----------------	----------------	------------------	-----------------	---------------

025292	CBS™ High Security embryo and sperm straw with tripartite plug 0.3 ml	20
024856	Box of 100 Sterile filling nozzle for CBS™ High Security straws	

Identification and obturating rods for PETG straws

Blister pack of 20 sealing and identification rods (42 mm) for 91 mm PETG straws

Yellow 007437	Violet 007438	Red 007440	Orange 007442	Pink 014484
Blue 014485	Grey 014486	Green 014487	Royal Blue 014488	White 014489

007342	Blister pack of 20 sterile yellow sealing and identification rods (13 mm) for 133 mm PETG straws
--------	--



ACCESSORIES

2D colored inserts

Bag of 500 inserts for CBS™ High Security Tubes

White 024108	Blue 024109	Green 024110	Yellow 024111	Red 024112	Pink 024113
-----------------	----------------	-----------------	------------------	---------------	----------------



026733	Bag of 20 sterile white inserts with 2D data for CBS™ High Security Tubes
--------	---

024114	Bag of 100 sterile white inserts with 2D data for CBS™ High Security Tubes
--------	--

BMP 21 and BMP 51 printers

024498 BMP 21 printer

025446 BMP 51 printer



BMP 21 PRINTER



BMP 51 PRINTER

DESCRIPTION

Identification of CBS™ High Security and CBS™ High Security Vitrification straws for BMP 21 and BMP 51. Additional option of CBS™ tube identification with the BMP 51. Brady labels are specially designed for harsh laboratory environments.

TECHNICAL CHARACTERISTICS

Print method: thermal transfer (lasting, no smearing).
Multiple line printing.

BMP 21 PRINTER

L x W x H: 228.6 x 114.3 x 63.5 mm

Weight: 0.750 kg

BMP 51 PRINTER

L x W x H: 262 x 91 x 152 mm

Weight: 1.2 kg

Service temperature: 4°- 49° C

FCC Class A approved (printer)

BMP 21 PRINTER

024500 220V adapter for BMP 21 printer

024499 BMP 21 printer case

024501 Polyester ribbon 9.5mm for BMP 21 printer

025453 Polyester ribbon 12.7 mm for BMP 21 printer

BMP 51 PRINTER

025450 Self-protected large label for CBS™ tube

025451 Self-protected small label for CBS™ tube

026433 Polyester ribbon 9.5mm for BMP 51 printer

026434 Polyester ribbon 12.7 mm for BMP 51 printer





STORAGE

Visotubes and goblets
Canisters
Identification rods for visotubes
Insulated transport box

Visotubes and goblets CBS™



DESCRIPTION

Freezing of biological samples in liquid nitrogen in straws, sorted by color codes. CBS High Security straws are inserted in visotubes, which are housed in colored goblets prior to being stored in the cryopreservation units. Goblets come in 8 different colors and their sub-compartments (visotubes) come in 12 different colors.

The Daisy goblet holds 12 visotubes and can hold a maximum of 168 CBS High Security 0.3 and 0.5 mL straws.

TECHNICAL CHARACTERISTICS


Diameter: 65 mm (67 mm with lid)

Goblet height: 117 mm

Total height of the Daisy goblet (with cover): 135 mm

Height of triangular visotubes: 120 mm

Height of round visotubes with 17.5 mm diameter: 133 mm



C O L O R S	Transparent	006924	-	021224	021366	006321	015144	015152
	Black	-	018153	-	-	-	-	-
	Brown	-	018147	-	-	-	-	-
	Red	-	018146	021228	-	-	015146	015154
	Green	-	018145	021226	-	-	015147	015155
	Blue	-	018148	021225	-	-	015151	015159
	Grey	-	018144	026948	-	-	018141	018142
	Violet	-	018152	021229	-	-	015150	015158
	Yellow	-	018143	021227	-	-	015148	015156
	Pink	-	018149	-	-	-	-	-
	Orange	-	018150	-	-	-	-	-
	Pistachio	-	018151	026949	-	-	015149	015157
PACKAGING		100	100	10	50	10	1	5
C A P A C I T Y	PETG 0.25 mL straw	55	45	820	-	-	540	540
	PETG 0.5 mL straw	20	20	365	-	-	240	240
	HSV CBS™ High Security straw	20	20	365	-	-	240	240
	High Security CBS™ straw	14	14	225	-	-	168	168

Visotubes and goblets CBS™



DESCRIPTION

Freezing and storage of biological materials in straws. Arrangement using color coding of straws prior to storage in liquid nitrogen.

- Standard goblet Ø 35 mm
Diameter: 35 mm
Height: 122 mm
- Standard goblet Ø 65 mm
Diameter: 65 mm
Height: 117 mm
- Polygonal, hexagonal and round visotubes
Height: 120 mm

All visotubes are also available in bags of 300 units (in identical colors and diameters).

			Polygonal visotube	Hexagonal visotube	Round visotube Ø 7,1 mm	Round visotube Ø 9,2 mm	Round visotube Ø 10 mm	Round visotube Ø 12 mm	Round visotube Ø 13 mm	Goblet Ø 35 mm	Goblet Ø 65 mm
C O L O R S	White	○	020470	020486	020492	020499	020505	020511	020517	020523	024392
	Blue	●	020472	020487	020493	020500	020506	020512	020518	-	006755
	Green	●	020482	020488	020494	020501	020507	020513	020519	-	006754
	Yellow	●	020483	020489	020495	020502	020508	020514	020520	-	006756
	Orange	●	020484	020490	020496	020503	020509	020515	020521	-	-
	Red	●	020485	020491	020497	020504	020510	020516	020522	-	006397
	Violet	●	-	022141	-	-	-	-	-	-	006757
	Pistachio	●	-	-	-	-	-	-	-	-	006753
PACKAGING			10	10	10	10	10	10	10	10	10
C A P A C I T Y	PETG straw 0.25 mL		30	90	7	10	14	22	27	200	820
	PETG straw 0.5 mL		15	36	2	5	5	8	10	94	365
	HSV CBS™ High Security straw		14	36	3	6	6	10	12	-	-
	CBS™ High Security straw		8	22	1	3	4	7	7	75	225
	In a goblet Ø 35 mm		4	1	15	10	8	5	5	-	-
	In a goblet Ø 65 mm		15	7	60	37	31	21	19	-	-

STORAGE

Canisters



DESCRIPTION

Canisters are cylindrical racks for keeping goblets in liquid nitrogen or nitrogen vapors. The goblet and canister storage concept is compatible with all types of nitrogen and electric freezers. Five canister lengths are available, with a capacity of between 2 and 6 goblets. A colored flag can be placed on the lifter (a bent metal rod to lift the stack of goblets) for quick identification of each canister. Canisters are stored in the nitrogen freezer before filling it with liquid nitrogen. Goblets are stacked and removed one by one with the lifter. Goblets must be handled in the cold environment of the neck of the nitrogen freezer to ensure even sample temperature.

TECHNICAL CHARACTERISTICS

Diameter: 70 mm

Canister with handle for standard goblets ø 65 mm without cover					1
2-shelf	3-shelf	4-shelf	5-shelf	6-shelf	
007147	007148	007149	007150	007151	

Canister with handle and white flag for Daisy goblets					1
2-shelf	3-shelf	4-shelf	5-shelf	6-shelf	
008644	008645	008646	007198	007199	

Plastic handle (colored flag)					10
White	Yellow	Salmon	Pink	Dark Green	
007328 ○	015693 ●	015694 ●	015695 ●	015696 ●	
Turquoise	Orange	Violet	Grey		
015697 ●	015698 ●	015699 ●	015706 ●		

014175	Permanent black markers	2
026924	Medium forceps 23 cm	1
026925	Long forceps 110 cm	1
022112	Rack for 24 daisy goblets	1
021998	Rack for 32 daisy goblets	1



Identification rods for visotubes



DESCRIPTION

These ID rods are a little bit longer than straws and are used to identify individual visotubes.

Medium identification rods for visotubes

100

Yellow 006331	White 006762	Red 006763	Grey 006774	Orange 006775	Pink 006876
------------------	-----------------	---------------	----------------	------------------	----------------

Mini identification rods for visotubes

100

White 006330	Yellow 006332	Red 006777	Pink 006779	Orange 006786	Grey 006787
Blue 006782	Pistachio 006783	Turquoise 023872	Mauve 023871	Mastic 023870	

Insulated transport box

015937 Bag of 5 insulated boxes



DESCRIPTION

Sperm transport prepared for intrauterine insemination. HDPE box with a precut polyurethane foam to hold a tube. These dimensions are compatible with all round or cone-shaped 5-15 mL culture tubes.

Two hours before use, the box can be placed in an incubator at 37°C to maintain an optimum temperature when transporting a tube containing sperm prepared in the laboratory for the insemination clinician. The box is suitably insulated to preserve sperm motility.

TECHNICAL CHARACTERISTICS

Length: 120 mm
Diameter: 65 mm



EQUIPMENT

Nano-Digitcool
Digitcool controlled-rate freezers
Craft™ pump
SYMS
SYMS III
SYSO
PACE
MAPI
DIVA
Integral HSV



Nano-Digitcool

CE marked

025680 Nano-Digitcool



DESCRIPTION

The compact controlled rate freezer solution for daily use for all cryopreservation applications.

Digitcool freezers are used for controlled-rate freezing of biological samples (plasma, blood cells, tissue, gametes, etc.). Stainless steel Digitcool freezers are easy to maintain and disinfect. They are easy to set up and allow the user to optimally control the various protocols.

- Vertical nitrogen flow with vaporization
- Standalone operation available (emergency mode without IT)
- Traceability: CryoBioSoft software (aligned CFR21)
- Freezing of bags, straws, tubes, etc.
- Display of freezing phases, results and archives

TECHNICAL CHARACTERISTICS

Weight: 55 Kg

Dimensions: 772 x 475 x 472mm

Chamber dimensions (inside): 238 x 178 x 200mm

Volume: 11.5 L

Capacity:

- 33 CBS High Security straws/
- 192 2 mL tubes
- 15 DF200 bags

Power: 1200 W

Voltage: 220 V / 50Hz / 8 A



- 025433 Tubes rack for Nano-Digitcool**
- 024572 Straws rack for Nano-Digitcool**
- 025327 DF 200 bags rack for Nano-Digitcool**
- 025433 96 CBS™ Tubes rack**

Digitcool controlled-rate freezers

007209	Digitcool
007210	Mini-Digitcool
007208	Micro-Digitcool
025680	Nano-Digitcool



DESCRIPTION

Digitcool freezers are used for controlled-rate freezing of biological samples (plasma, blood cells, tissue, gametes, etc.). Stainless steel Digitcool freezers are easy to maintain and disinfect. They are easy to set up and allow the user to optimally control the various protocols.

ADVANTAGES

- Temperature range: +50°C to -150°C
- Cooling rate: 0.1 to 60°C/min
- Automatic reheating, drying and return to room temperature at the end of the cycle
- Programmer/regulator, hot/cold regulator and plug-in
- Temperature measured by PT 100 ohm (chamber and product)
- Digital temperature display (chamber, program)
- Can be connected to a computer terminal (portable or desktop) with control using the Cryobiosoft software package
- Regulation based on "chamber" temperature
- Liquid nitrogen dispensed through a self pressurized reservoir with a 60 or 120 liter capacity (with minimum pressure of 1 bar)

	Digitcool	Mini-Digitcool	Micro-Digitcool	Nano-Digitcool
External dimension	1170x800x1000mm	770x510x730mm	600x380x520mm	722x475x472mm
Weight	130 kg	58 kg	38 kg	55 kg
Internal dimension	960x470x320mm	640x320x420mm	490x325x230mm	238x178x200mm
Volume	150 L	90 L	26 L	11.5 L
Sample capacity	3 000 CBS straws 2304 CBS tubes 32 DF200 bags / 32 DF700 bags	1 392 CBS straws 576 CBS tubes 32 DF200 bags / 16 DF700 bags	240 CBS straws 192 CBS tubes 15 DF200 bags / 9 DF700 bags	33 CBS straws 192 CBS tubes 15 DF200 bags
Power	2500 W	2000 W	1000 W	1200 W
Voltage	220V/50Hz/16A	220V/50Hz/10A	220V/50Hz/6A	220V/50Hz/6A

025433	96 CBS™ Tubes rack
025109	9 pouches rack 150 mL for Micro-Digitcool

Craft™ pump

005553 Craft™ pump - Rocket vacuum pump (comes with accessories)



DESCRIPTION

Aspiration of follicular fluid and oocytes.
The Craft™ pump is specially designed for gentle and controlled aspiration, at a preset negative pressure, of oocytes by follicular aspiration.

TECHNICAL CHARACTERISTICS

Dimensions (L x W x H): 20 x 14 x 12 cm

Weight: 3.2 kg.

Pressure: 0 - 400 mm Hg

- 015621 Craft™ pump foot switch
- 006553 Craft™ pump tubing
- 018204 Craft™ pump tank
- 018268 Craft™ pump tank plug
- 019270 Luer-Lock connector for Craft™ pump tubing

SYMS

016399 SYMS sealer



DESCRIPTION

Manual sealer for CBS™ High Security straws.
Cryo Bio System has developed a sealer for CBS™ High Security straws in ionomeric resin. The sealer is connected to the mains and operated by a push-button or foot switch as desired.

TECHNICAL CHARACTERISTICS

Dimensions (L x W x H): 230 x 220 x 170 mm

Weight: 6 kg

Power supply : 220 V / 60 ou 50 Hz

009848 SYMS spare parts kit

SYMS III

CE marked

025547 SYMS III sealer



DESCRIPTION

Sealer for CBS™ High Security straws, tubes and vitrification straws.

The SYMS III sealer is designed to heat seal CBS™ High Security 0.3 ml, 0.5 ml and CBS™ High Security Vitrification straws, and the CBS™ High Security tube, for optimal cryopreservation of biological samples.

TECHNICAL CHARACTERISTICS

Dimensions (L x W x H): 335 x 250 x 105 mm

Weight: 3 kg

Power supply: 110 ou 220 V / 60 ou 50 Hz

FEATURES

- Multilingual interface (French, English, Spain and Chinese) + 4 optional languages
- Color touch screen compatible with the use of laboratory gloves
- Machine cycle display: pre-heating, ready status and sealing in progress
- Two sealing modes: automatic detection or operator-controlled via the touch screen
- Fault signal with messages and alarms
- Display and tracking of maintenance modes
- Easy to clean and service.



EQUIPMENT

026550 Set of sealing jaws for SYMS III



DESCRIPTION

Automatic CBS High Security tube opening device.

The SYSO opening device can be used under laminar flow and is designed to open CBS High Security tubes with a hot wire.

- The carousel can hold up to 6 CBS High Security tubes (opening individually or in succession).
- User-friendly touch screen
- 8 languages available
- The wire is systematically sterilized by pyrolysis after each tube is opened.

TECHNICAL CHARACTERISTICS

Dimensions (L x W x H): 358 x 275 x 157 mm

Weight: 2.5 kg

Power supply: 110 ou 220 V / 60 ou 50 Hz

FEATURES

The SYSO opening machine is a worktop device for lab benches which can be used under laminar flow. It uses a hot wire to open CBSTTM High Security Tubes and has applications which include:

- Epidemiological research departments
- Biobanks
- Serum banks
- Cellular and gene therapy units
- Vaccine-manufacturing pharmaceutical companies (living cells)
- Gene banks (animal, plant, microbiological)
- Reproductive biology laboratories
- Gamete and gonadal tissue banks



PACE

018451 PACE 220 V / 50 Hz
018450 PACE 110 V / 60 Hz



DESCRIPTION

Semi-automatic system for filling biological samples into CBS™ High Security straws.

From a sample primary tube, PACE fills CBS™ High Security straws and automatically seals both ends of CBS™ High Security 0.3 or 0.5 ml straws, which can be pre-identified.

PACE is the ideal CBS™ robot for medium to large-scale projects with preset archiving protocols. PACE is compatible with CBS™ High Security straws - pre-printed or not - with bar code or alphanumerical code.

The system comprises a filling and sealing unit with control unit.

TECHNICAL CHARACTERISTICS

• PACE

Dimensions (L x W x H): 380 x 300 x 370 mm

Weight: 25 kg

• Control Unit

Dimensions (L x W x H) : 410 x 365 x 155 mm

Weight: 14 kg

Power supply:

110 or 220 V / 60 or 50 Hz

EQUIPMENT

007454	Sterile CBS™ injection tubing (5 x 10)	50
018620	Box of long sterile CBS™ injection tubing	25
007451	Sterile CBS™ aspiration tubing (5 x 10)	50
014623	Non sterile injection tubing	200
018276	Non sterile long blue CBS™ injection tubing	200
014621	Non sterile aspiration tubing	200

MAPI

007218 MAPI



DESCRIPTION

Automatic biological sample filling and identification system for CBS High Security straws.

From a primary tube, MAPI automatically fills, seals, prints out and validates the identification of CBS 0.3 or 0.5 mL straws (bar code or alphanumerical data).

MAPI features a filling robot, a control unit, a special liquid nitrogen ink-jet type printer and a PC with the MAPI pilot software. The robot is placed on a special lab bench at ergonomical height.



TECHNICAL CHARACTERISTICS

- MAPI
Dimensions (L x W x H): 760 x 260 x 470 mm
Weight: 35 kg
- Worktop
Dimensions (L x W x H): 1200 x 600 x 900 mm
Height with machine: 1260 mm
Weight with machine: 102 kg
- Control unit
Dimensions (L x W x H): 430 x 380 x 190 mm
Weight: 14 kg
- Domino printer
Dimensions (L x W x H): 650 x 450 x 375 mm
Weight: 20 kg
Active printer vapor extractor duct, not included (diameter: 80 mm)
Power supply:
110 or 220 V / 60 or 50 Hz

007454	Sterile CBS™ injection tubing (5 x 10)	50
018620	Box of long sterile CBS™ injection tubing	25
007451	Sterile CBS™ aspiration tubing (5 x 10)	50
014623	Non sterile injection tubing	200
018276	Non sterile long blue CBS™ injection tubing	200
014621	Non sterile aspiration tubing	200

DIVA

020984 DIVA with Domino printer
020983 DIVA without printer



DESCRIPTION

Automatic straw filling and positive identification of biological samples. Using a primary sample tube, DIVA fills and seals CBS High Security 0.5 mL straws (standard plug). It also prints and validates the identifier (bar code GS1 128 or alphanumerical code) on each straw.

A color sorting system collects the straws to store the production in Daisy goblets.

TECHNICAL CHARACTERISTICS

- L x W x H : 1208 x 660 x 1600 mm
- Weight: 100 kg without printer
- Electrical consumption: 400 W
- Power supply: 110 or 220 V
- Frequency: 60 or 50 Hz
- Service temperature: +15°C to +32°C
- Maximum elevation: 2 000 m
- Relative humidity: 80% at +32°C



Integral HSV

027807 Integral HSV Vitrification unit



DESCRIPTION

The INTEGRAL HSV vitrification unit is designed for vitrification, packaging and opening of CBS High Security straws in Reproductive Biology Laboratories.

TECHNICAL CHARACTERISTICS

Width: 283 mm

Length: 487 mm

Height: 265 mm with cover, 222 mm without

Chamber volume: 5L

Weight : 5 kg

- 027636 Box of 5 opening devices for CBS™ High Security Vitrification straw
027172 Opening set (holder + device) for CBS™ High Security Vitrification straw




DESCRIPTION

The opening device for CBS™ High Security Vitrification straws has been designed exclusively to open CBS™ High Security Vitrification straws. It is an ambidextrous device. It can be held either directly in the hand or using a “holder” (an accessory designed to keep the user further from the liquid nitrogen)

Blister of 4 CBS™ High Security Vitrification straws

Red	White	Yellow	Pink	Blue	Green
025246	025247	025248	025249	025250	025251



DESCRIPTION

The High Security Vitrification straw is made of ionomeric resin, a capillary tube with a clear runner, co-injected with its colored handling rod, and a blue insertion device.

For more information: p. 10-11



Connected to... **LIFE SCIENCES**



www.cryobiosystem.com
contact@cryobiosystem-imv.com

Cryo Bio System
ZI n°1 Est
61300 L'Aigle
+33 (0)233 346 464
contact@cryobiosystem-imv.com

Cryo Bio System Netherlands
Nifa Technologies
Pallasweg 22
8938 AS Leeuwarden
+31 58 2123279
www.nifa.nl
info@nifa.nl

Cryo Bio System Italy
Via Stefano Merli
29122 Piacenza
+39 0523 36 00 10
info@imv-technologies.it

Cryo Bio System USA
11725 95th Avenue North
Maple Grove, MN 55369
+1 763 488 1881
contact@imvusa.com

Cryo Bio System India
Plot No 750, Phase V, Udyog Vihar
Gurgaon 122016 (Haryana)
+91 124 400 44 30/31/32
contact@imvindia.com

Cryo Bio System China
Floor 12, Building A,
No. 400 Pudian Road,
Pudong, Shanghai 200122
+86 21 50586948,
contact@imvchina.com

Leja
Luzernestraat 10
2153 GN Nieuw-Vennep
Pays Bas
+31 (0)252-621 848
www.leja.nl
info@leja.nl